Power Amplifiers

Limit Pro

Professional Equipment

FPAG02

LIMIT PROFESSIONAL

Output Power:	Stereo 8ohm (1kHz; THD <0.2%) 250W
Output Power:	Bridged 8ohm (1kHz; THD <0.2%) 800W
Output Power:	Stereo 4ohm (1kHz; THD <0.2%) 400W
Output Voltage:	8ohm (1kHz; THD <0.2%) 45V
Output Voltage:	4ohm (1kHz; THD <0.2%) 40V
Gain:	31.2dB
S/N Ratio:	>95dB
Residual Noise:	<70dB: ATT min
Power Consumption:	Unloaded 70W
Power Consumption:	8ohm Loaded 250W
Power Consumption:	Full Loaded 1400W
Fuse AC230V 50Hz:	T6.3A
Sensitivity:	0.775V RMS
Input Impedance:	10k ohm (Unbalanced Input)
Frequency Response:	20Hz-20kHz
Frequency Response:	20k ohm (Balance Input)
Channel Seperation:	>60dB (1kHz)
Channel Seperation:	>50dB (10kHz)
Max. Input Level:	+18dB
Distortion:	<0.01% 1/3 Fixed Power 4ohm 1kHz
Slew Rate 8£ [Full Swing] (Stereo & Bridge):	+/-40V
Dimensions WxDxH:	48.3x41.5x88.0 cm
Weight:	17.5 kg/pc
Measurement LxWxH:	57.0 x 56.0 x 20.5 cm
Packing:	20.0 kg
Net Weight:	18.0 kg

Pierre Corneliskaai 17 ✍ B-9300 Aalst ✍ Belgium ✍ www.limitgroup.com